

Floorstanding cistern, two-part Universal for floorstanding WC pan
82966.0



TECHNICAL DATA

Order no.	82966.0
Certified to	EN 14055
matching for	Floorstanding WC pan rimless, order no. 82333.6, 82333.7
Specification	Floorstanding, consisting of two-parts Flushing mechanism Dual-Flush water condensation insulation Charge 882 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	side left, side right, 3/8" brass
Weight	21,0 kg
Mounting acc. incl.	Fastening kit, order no. 89852.6
Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN- connection, order no. 89009.2 for VARIO-outlet 220 - 305 mm only LAUFEN- connection, order no. 89902.5 Angle valve for water inlet Water inlet hose

Colours see colour table

SPECIFICATION TEXT

Floorstanding cistern, two-part Universal Laufen-KARTELL BY LAUFEN,
sanitary ceramic
EN 14055
dimensions 400/410 x 140 x 980 mm
Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
water inlet side left, side right, 3/8" brass
matching floorstanding WC pan rimless, order no. 82333.6, 82333.7
Special feature: water condensation insulation
Order no. 82966.0

TECHNICAL DRAWINGS / S 1 : 20

