

Floorstanding cistern Universal for floorstanding WC pan
82866.1



TECHNICAL DATA

Order no.	82866.1
Certified to	EN 14055
matching for	Floorstanding WC pan rimless, order no. 82333.6
Specification	floorstanding Flushing mechanism Dual-Flush water condensation insulation Charge 881 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	concealed top left rear, 1/2" brass
Weight	21,5 kg
Mounting acc. incl.	Fastening kit Angle valve for rear water inlet Water inlet hose
Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-

connection, order no. 89009.2
 for VARIO-outlet 220 - 305 mm only LAUFEN-
 connection, order no. 89902.5

Colours see colour table

SPECIFICATION TEXT

Floorstanding cistern Universal KARTELL BY LAUFEN, sanitary ceramic
 EN 14055
 dimensions 400/410 x 140 x 980 mm
 Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
 concealed water inlet top left rear, 1/2" brass
 matching floorstanding WC pan rimless, order no. 82333.6
 Special feature: water condensation insulation
 Order no. 82866.1

TECHNICAL DRAWINGS / S 1 : 20

